



in touch with tomorrow



DISCLAIMER: These instructions are suggested installation procedures only. Electric Zone Inc. assumes no liability for problems, damages, injuries, or expenses that may occur from improper installation or product failure. These instructions do not constitute professional installation and may not necessarily meet all electrical requirements in your state. If you are uncomfortable with any of these procedures please contact a licensed electrical contractor.

5050 120V SMD LED STRIP LIGHT INSTALLATIONS

165' SPOOL 120V SMD LED ACCESSORIES:

- A** 1x 120V SMD LED Power Cord
- B** 1x 120V SMD LED Power Connector
- C** 1x End Cap
- D** 50x Mounting Clips



Never attempt to cut or install other accessories while SMD LED strip lights are plugged in to a power source.



If you follow the strip light approximately 19.5" from the end, you will find a gap in the internal white tape that indicates where to make your cut.



Use any generic brand rope light cutters or other heavy duty shears to make a perpendicular cut between bulbs in the center of the gap.

ADDITIONAL 120V SMD LED STRIP LIGHT ACCESSORIES:

LED Dimming Controller
LED Flashing Controller
LED Fading Controller
5050 120V SMD LED Inline Splice
Silicone Sealant



Always insert sharp pins into strip light and rounded pins into accessories.



WARNING: IF USING STRIP LIGHTING OUTDOORS, BE SURE TO USE WATERPROOF PVC OR SILICON TO SECURE ALL CONNECTIONS AND POWER CORDS.



CUTTING INTERVALS:

The length of your 120V SMD LED strip light is customizable and may be cut to size in 19.5" intervals only.

CONNECTING THE POWER CORD:

- 1** Line up the sharp prongs of the power connector with the strip light wires.
- 2** Gently insert power connector into the end of the strip light.
- 3** Optional: Use PVC or silicone sealant to secure and/or waterproof all connections.
- 4** Insert rounded prongs of power connector into the power cord.
- 5** Attach an end cap to end of the strip light run. (If not previously installed)



USING A 5050 SMD LED SPLICE:

- 1** Align built in power connector pins with corresponding 120V SMD LED strip light wires.
- 2** Gently insert each end of the 120V SMD LED strip light into the splice.
- 3** Optional: Use PVC or silicone sealant to secure and/or waterproof all connections.
- 4** Attach an end cap to the end of strip light run. (If not previously installed)



NOTE: LED STRIP LIGHTS ARE POLARIZED. IF THEY DO NOT LIGHT UP WHEN YOU FIRST PLUG THEM IN, QUICKLY UNPLUG THE POWER CORD AND FLIP THE POWER CONNECTOR 180° OR INSERT THE POWER CONNECTOR IN THE OPPOSITE END OF THE STRIP LIGHT.

