



Incredible **70,000** hrs

GENERAL DESCRIPTION

Neptun's LED bollard features a traditional style to make it an excellent choice for new construction or retrofit applications. The LED-98 series offers excellent illumination and uniformity. It can replace existing HID & HPS fixtures up to 100W.

APPLICATION

- Security Lighting
- Area Lighting
- Walkway Lighting

STRUCTURE, MATERIALS, & FEATURES

- Fiberglass reinforced composite housing for excellent durability and strength.
- High Efficiency, heat and impact resistant, UV protected, non-yellowing clear polycarbonate lens.
- Corrosion resistant electrocoat finish (custom colors available).
- Continuous silicone gasketing surrounds lens for weather - tight seal.
- Self-ballasted LED lamp included.
- Instant-On flicker-free Cold Start and Hot Re-Start.
- High quality glare-free light with high CRI above (83).
- Bright white light (5000°K) for greater visibility and safety.
- Advance phosphors for high lumen output and high lumen maintenance.
- Up to 15 year maintenance free operation.
- 5 Year Warranty.

ORDERING INFORMATION

Sample Number: LED-98020-43R-UNV-850-BLK
Custom options and accessories available. Please consult factory

Series	Lamp Wattage	Type	Voltage	Color Temp.	Color
LED-98 = Bollard	015 = 15 W 020 = 20 W 025 = 25 W	43R = 43" Rounded Top 43F = 43" Flat Top	UNV = 120-277VAC	830 = 3000°K 841 = 4100°K 850 = 5000°K * * Standard	BLK = Black BRZ = Dark Bronze GRY = Gray



PRODUCT INFORMATION

Model No.	Description	Rated Watts	Input Watts	Initial Lumens	Universal Line Voltage (VAC)	Max Line Current (Amp) @ 120 - 277	THD	Power Factor	Weight
LED-98015-UNV	Bollard Fixture	15	16	1,350	120 - 277	0.13 - 0.05	<20%	>0.90	30 lbs
LED-98020-UNV	Bollard Fixture	20	21	1,800	120 - 277	0.17 - 0.07	<20%	>0.90	30 lbs
LED-98025-UNV	Bollard Fixture	25	26	2,250	120 - 277	0.21 - 0.09	<20%	>0.90	30 lbs

SPECIFICATIONS

- LED Driver Constant Current
- Power Supply 350mA
- Start Method InstantON
- Hot Re-start InstantON
- Universal Input Line Voltage 120-277 VAC
- Input Line Frequency 50/60 Hz
- Ballast Off-State Draw 0 Watts
- Sound Rating Class A
- ANSI Surge Protection Class A
- LED / Driver System Life 70,000 Hrs.
- Lumen Maintenance @50,000Hrs > 70%
- Color Temperature 5,000°K
- Color Rendering Index (CRI) > 80
- Minimum Starting Temperature -40°C
- Maximum Starting Temperature 50°C
- Lumens per Watt > 80
- Shock / Vibration Resistant Yes
- Power Factor > 0.90
- Total Harmonic Distortion < 20%
- Inrush Current Peak < 10 Amp
- FCC Compliance Part 18, Subp. C
- IP Rating IP65
- Warranty 5 Year

DRILLING PATTERN

