




Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at [www.designlights.org/qpl](http://www.designlights.org/qpl)

OUTDOOR RATED  
**IP66**

\*\* AVAILABLE \*\*

Bi-Level Dimming  
100% 50%

0 - 10V  
FULL DIMMING



Incredible **100,000** hrs

## GENERAL DESCRIPTION

Neptun's low-profile LED fixtures feature a sleek architectural design and durability to be used in new construction or retrofit applications. The LED-49 series fixture features excellent optics and its rugged design allows for use in a variety of indoor and outdoor applications. It can replace existing HID & HPS fixtures up to 320 Watts.

## APPLICATION

- Indoor Low/High Bay Lighting
- Canopy Lighting
- Freezer Lighting
- Gas Station Lighting
- Storage Lighting
- Security Lighting
- Area Lighting
- Tunnel Lighting

## STRUCTURE, MATERIALS, & FEATURES

- Heavy-gauge, die-cast aluminum housing with cooling fins.
- Heat and impact resistant tempered glass lens with anti-glare diffuser.
- Corrosion resistant electrocoat dark grey finish (custom colors available).
- Continuous silicone gasket surrounds lens for weather - tight seal.
- Various mounting options available.
- High Output COB LED's.
- High power factor, low THD driver with 6kV/3kA surge protection.
- High performance Thermal Management system.
- Instant-On flicker-free Cold Start and Hot Re-Start.
- Bright white light (5000°K) for greater visibility and safety.
- Up to 15 year maintenance free operation.
- 5 Year Warranty on complete fixture. (LED's, Driver, & Housing)
- **Optional:** Bi-Level Dimming, 0-10V Dimming, Wi-Fi Control, Remote Monitoring and ON/ OFF Control

## ORDERING INFORMATION

Sample Number: LED-49125-24-UNV-0-10VDIM-750-MD-PDM-C3  
Custom options and accessories available. Please consult factory

Series	Wattage	Voltage	Options	CCT	Accessories	Options
<b>LED-49</b> = Low-Profile	<b>125-24</b> = 125 W <b>135-24</b> = 135 W <b>150-24</b> = 150 W	<b>UNV</b> = 120-277 VAC <b>347V</b> = 347 VAC <b>480V</b> = 480 VAC	<b>0-10VDIM</b> = 0-10V Dimming <b>BL-DIM</b> = Bi-Level Dimming * * Includes Motion Sensor ** Contact Factory for dimming options	<b>735</b> = 3500°K <b>741</b> = 4100°K <b>750</b> = 5000°K * * Standard	<b>MD</b> = Motion Sensor ON/OFF <b>DLH</b> = Day Light Harvesting* <b>GPPL</b> = Gripple Hangers <b>PDM</b> = Pendant Mount * Used with 0-10V Dimming **See pg. 2 for mounting	<b>C3*</b> = 3' Cord-No Plug (other lengths available C6 = 6' cord) <b>PC3</b> = 3' Cord with NEMA Plug (verify plug type when ordering) * Standard



## PRODUCT INFORMATION

Model No.	Description	Rated Watts	Input Watts	Delivered Lumens	Universal Line Voltage (VAC)	Max Line Current (Amp) @ 120 - 277	THD	Power Factor	Weight
LED-49125-24-UNV	Low Profile LED Fixture	125	127	15,000	120-277	1.09 - 0.47	<20%	>0.90	32 lbs
LED-49135-24-UNV	Low Profile LED Fixture	135	137	16,200	120-277	1.18 - 0.51	<20%	>0.90	32 lbs
LED-49150-24-UNV	Low Profile LED Fixture	150	155	18,000	120-277	1.31 - 0.56	<20%	>0.90	32 lbs

## SPECIFICATIONS

- Driver ..... Constant Current
- Start Method ..... InstantON
- Hot Re-start ..... InstantON
- Power Supply ..... 350mA
- Driver UL Rating ..... Class 1
- Driver UL Outdoor Rated ..... Wet Location
- Sound Rating ..... Class A
- ANSI Surge Protection ..... IEEE C62.41 C High
- Driver Off-State Draw ..... 0 Watts
- Universal Input Line Voltage ..... 120-277 VAC
- Input Line Frequency ..... 50/60 Hz
- Projected (L70) @ 25°C ..... > 100,000 hrs.
- Color Temperature ..... 5,000°K
- Color Rendering Index (CRI) ..... > 80
- Minimum Starting Temperature ..... -40°C
- Maximum Starting Temperature ..... +50°C
- Lumens per Watt ..... > 100
- Shock / Vibration Resistant ..... ANSI-C136.31.
- Power Factor ..... > 0.90
- Total Harmonic Distortion ..... < 20%
- Inrush Current Peak ..... < 10 Amp
- FCC Compliance ..... Part 15, Subp. C
- ETL Listed / UL Standard 1598 ..... Yes
- Housing IP Rating ..... IP66
- Driver IP Rating ..... IP67
- Warranty ..... 5 Year


## MOUNTING OPTIONS

Surface Mount



Adjustable Mounting Brackets (Standard)

Hanging Mount




Supplied with Gripple Hangers (GPPL)



Pendant Mount  
3/4" K.O. (PDM)  
Pendant Not Included

## PHOTOMETRICS (See Complete IES File)



Type V Distribution