



Incredible **100,000 hrs**

GENERAL DESCRIPTION

Neptun's LED Wall Mount fixtures feature architectural design and durability to fit new construction and retrofit applications. The LED-212 series feature high output LED's and custom engineered optics to provide excellent uniformity and efficiency. They can replace existing HID & HPS fixtures up to 50W.

APPLICATION

- Building Accent Lighting
- Building Facade Lighting
- Accent Lighting
- Landscape Lighting
- Security Lighting
- Stairwell Lighting

STRUCTURE, MATERIALS, & FEATURES

- Heavy-gauge, die-cast aluminum housing.
- Heat and impact resistant sealed glass lens around optics.
- Corrosion resistant electrocoat bronze finish (custom colors available).
- Correlated Color Temperature of (5000°K) for greater visibility and safety.
- High Output COB LED's with borosilicate glass lens optics.
- High power factor, low THD driver with 6kV/3kA surge protection.
- InstantON flicker-free Cold Start and Hot Re-Start.
- Up to 15 years Maintenance free operation.
- 5 Year Warranty on complete fixture. (LED's, Driver, & Housing)

ORDERING INFORMATION

Sample Number: LED-212010-UNV-850-BRZ
Custom options and accessories available. Please consult factory

| Series | Wattage | Voltage | Color Temp | Color |
|----------------------|------------|-------------------|--------------------------------------------------------------|--------------------------------------------------|
| LED-212 = Wall Mount | 010 = 10 W | UNV = 120-277 VAC | 835 = 3500°K 841 = 4100°K 850 = 5000°K * * Standard | BRZ = Dark Bronze ■ * Custom Colors Available |



PRODUCT INFORMATION

| Model No. | Description | Rated Watts | Input Watts | Delivered Lumens | Universal Line Voltage (VAC) | Max Line Current (Amp) @ 120 - 277 | THD | Power Factor | Weight |
|----------------|------------------------|-------------|-------------|------------------|------------------------------|------------------------------------|------|--------------|--------|
| LED-212010-UNV | LED Wall Mount Fixture | 10 | 11 | 800 | 120-277 | 0.08-0.03 | <20% | >0.90 | 5 lbs |

SPECIFICATIONS

- Driver Constant Current
- Start Method InstantON
- Hot Re-start InstantON
- Power Supply 350mA
- Driver UL Rating Class 1
- Driver UL Outdoor Rated Wet Location
- Sound Rating Class A
- ANSI Surge Protection IEEE C62.41 C High
- Driver Off-State Draw 0 Watts
- Universal Input Line Voltage 120-277 VAC
- Input Line Frequency 50/60 Hz
- Projected (L70) @ 25°C > 100,000 hrs.
- Color Temperature 5,000°K
- Color Rendering Index (CRI) > 80
- Minimum Starting Temperature -40°C
- Maximum Starting Temperature +50°C
- Lumens per Watt > 80
- Shock / Vibration Resistant Yes
- Power Factor > 0.90
- Total Harmonic Distortion < 20%
- Inrush Current Peak < 10 Amp
- FCC Compliance Part 15, Subp. C
- Housing IP Rating IP65
- Driver IP Rating IP67
- Optics IP Rating IP68
- Warranty 5 Year

MOUNTING OPTIONS

