



### Applications:

- Ceiling Interior
- Pendant Exterior
- Canopy Parking Garage

### Description:

The LBSS slim form rivals most square canopy fixtures. Surface or Pendant mount, it gets the light where you need it.

### Details:

- IP Rating IP67
- Materials Die Cast Aluminum
- Lens Acrylic
- LM70 Life 100,000 Hours
- Warranty 7 Years
- CRI 83+
- Certification UL, DLC 4.2, FCC, CE, RoHS
- Driver Man. Mean Well
- Chip Man. Phillips

### Electrical:

- Power Factor 0.99
- Frequency 50/60 Hz
- Max THD (%) 15
- Operating Temp. -30° F to 130° F  
-34° C to 54° C
- Dimming 3 in 1 (Resistance, PWM, 1-10V)

- Height: 3.94 in / 100 mm
- Width: 10.43 in / 256 mm
- Length: 10.43 in / 256 mm
- Weight: 6.0 lb / 2.72 kg



LOW BAY SLIM SERIES

## Ordering Information

Series: LBSS

DLC Family: U-LCPN

Wtg	Lumen Pckge	Color Temp.	Distribution	Input Voltage	Mounting	Options	Finish
28	130 L/W	30K - 3000K	1 - 120°	1 - 120-277V	F - Flush	WP - 4' Whip MS - Motion Sensor	BL - Black
40	145 L/W	40K - 4000K		2 - 480V	P - Pendant		BZ - Bronze
60		50K - 5000K					
90		57K - 5700K					SP - Other

Example: LBSS-60-130-50K-1-2-P-WP-BL

Input Wattage:	28W	40W	60W	90W
Equivalent:	100W MH	175W MH	200W MH	250W MH

### Standard Colors



### Custom Colors



Notes:  
 • Only 5000K in black are stocked locally, check for ETA's

**Lumen Output**

System Watts	CCT	Lumens	LPW	Lumens	LPW
28	3000K	3,484	124	3,916	140
	4000K	3,556	127	3,997	143
	5000K	3,548	127	3,988	142
	5700K	3,612	129	4,060	145
40	3000K	4,862	122	5,551	139
	4000K	4,960	124	5,663	142
	5000K	5,040	126	5,754	144
	5700K	5,080	127	5,800	145
60	3000K	7,473	125	8,272	138
	4000K	7,680	128	8,501	142
	5000K	7,800	130	8,634	144
	5700K	7,860	131	8,700	145
90	3000K	11,365	126	12,390	138
	4000K	11,700	130	12,756	142
	5000K	11,880	132	12,952	144
	5700K	11,970	133	13,050	145



Multi-level motion sensor



Pendant Adapter

**Dimensions**

