



| | |
|-------------|--|
| DATE | |
| PROJECT | |
| TYPE | |
| NOTE | |
| PREPARED BY | |

CLA-MP

Architectural Exterior Wall Fixture



The **CLA-MP** is designed to bring efficiency while transforming the appearance of locations such as, convention centers, shopping centers, museums, entrances, walkways and any other exterior setting that seeks a modern, sophisticated look. This fixture is dark sky compliant and includes a wide light distribution.

FEATURES

- Life Rating: >200,000 (L70) hours for enhanced safety and maintenance
- Energy Savings: 80% compared to HID light sources
- IP55, Suitable For Wet Locations
- Light Output: 5000K
- Voltage: Standard 120-277V
- Applications: Exterior Walls, Entrances, Walkways, Convention Centers, Shopping Centers, Museums
- 10 Year Warranty
- Philips LED's and driver
- 10 KV Surge Protector

* Shown in custom finish



CONSTRUCTION

- Clear Tempered Glass
- Heavy Duty Aluminum Body

**PHILIPS
LUMILEDS**

| Model Number | INPUT POWER | LUMEN OUTPUT | SCOPTIC | COLOR TEMP (CCT) | CRI | RATED LIFE (L70) | INPUT VOLTAGE | INPUT FREQUENCY | HID Equivalent |
|---------------|-------------|--------------|---------|------------------|-----|------------------|---------------|-----------------|----------------|
| CLA-MP-5CLED | 7W | 757 | 1,249 | 5000K | 70+ | >200,000 | 120-277V | 50/60Hz | 35w HPS |
| CLA-MP-10CLED | 12W | 1,376 | 2,270 | 5000K | 70+ | >200,000 | 120-277V | 50/60Hz | 50w HPS |
| CLA-MP-15CLED | 20W | 1,918 | 3,068 | 5000K | 70+ | >200,000 | 120-277V | 50/60Hz | 70w HPS |
| CLA-MP-21CLED | 25W | 3,102 | 4,963 | 5000K | 70+ | >200,000 | 120-277V | 50/60Hz | 100w HPS |
| CLA-MP-30CLED | 35W | 4,128 | 6,604 | 5000K | 70+ | >200,000 | 120-277V | 50/60Hz | 150w HPS |

Ordering Guide Example: (CLA-MP-30CLED-50-MV-CUS-WC)

| CLA-MP | | | | | |
|--------|---|---|--------------------------------|--|---|
| MODEL | WATTS | COLOR TEMP | VOLTAGE | FINISH | OPTIONS |
| CLA-MP | 5W-5CLED 10W-10CLED 15W-15CLED 21W-21CLED 30W-30CLED | 27-2700K 30-3000K 35-3500K 40-4000K 50-5000K 57-5700K 65-6500K | MV=120-277V 480=480V | <u>STANDARD:</u> BZ-BRONZE <u>ADDITIONAL CHARGE:</u> GRY-GRAY BLK-BLACK WH-WHITE CUS-CUSTOM | HSS-HOUSE SIDE SHIELD EMR-EMR BATTERY WC-WIRELESS CONTROL PC-PHOTO CELL |

| | |
|-------------|--|
| DATE | |
| PROJECT | |
| TYPE | |
| NOTE | |
| PREPARED BY | |

CLA-MP

Architectural Exterior Wall Fixture

DIMENSIONS

