



Incredible **50,000** hrs

## GENERAL DESCRIPTION

Neptun's high performance LED PL lamps are designed for the replacement of existing PL fluorescent lighting systems. The LED-PL series are offered in a variety of color temperatures for flexibility in all types of applications. Very low temperature operation saves on HVAC costs and long life greatly reduces maintenance costs. The self-ballasted design allows for easy installation into most commonly used PL lamp system fixtures.

## APPLICATION

- Office Lighting
- School Lighting
- Healthcare Lighting
- Storage Lighting

## STRUCTURE, MATERIALS, & FEATURES

- Aluminum extruded backing for excellent thermal management.
- Correlated Color Temperatures of 3000°K, 4100°K, & 5000°K.
- Rotatable end caps.
- Mercury free design.
- No radiated EMI interference.
- High Output LED's.
- High power factor, low THD internal driver.
- InstantON flicker-free Cold Start and Hot Re-Start.
- Up to 15 years Maintenance free operation.
- 5 Year Warranty.

## ORDERING INFORMATION

Sample Number: LED-PL013-UNV-830-G24-2  
Custom options and accessories available. Please consult factory

Source	Series	Wattage	Voltage	Color Temp.	Base
LED = LED	PL = PL Lamp	013 = 13 W	UNV = 120-277 VAC	830 = 3000°K 841 = 4100°K 850 = 5000°K	G24-2 = G24 2 Pin



## PRODUCT INFORMATION

Model No.	Watts	Input Line Current (Amp) @ 120 - 277	Power Factor	THD	CCT (°K)	CRI	Lumens	Lm/W	Replaces	Base	Beam Angle
LED-PL013-UNV-830-G24-2	13	0.113-0.049	>0.90	<20%	3,000°	>80	1020	>80	23W	G24	120°
LED-PL013-UNV-841-G24-2	13	0.113-0.049	>0.90	<20%	4,100°	>80	1030	>80	23W	G24	120°
LED-PL013-UNV-850-G24-2	13	0.113-0.049	>0.90	<20%	5,000°	>80	1040	>80	23W	G24	120°

## SPECIFICATIONS

- LED Driver ..... Self-Ballasted
- Power Supply ..... 350mA
- Start Method ..... InstantON
- Hot Re-start ..... InstantON
- Universal Input Line Voltage ..... 120-277 VAC
- Input Line Frequency ..... 50/60 Hz
- Ballast Off-State Draw ..... 0 Watts
- Sound Rating ..... Class A
- ANSI Surge Protection ..... Class A
- LED / Driver System Life ..... 50,000 Hrs.
- Lumen Maintenance @ 30,000Hrs ..... > 70%
- Color Temperature ..... Various
- Color Rendering Index (CRI) ..... > 80
- Minimum Starting Temperature ..... -35°C
- Maximum Starting Temperature ..... 45°C
- Lumens per Watt ..... > 80
- Shock / Vibration Resistant ..... Yes
- Power Factor ..... > 0.90
- Total Harmonic Distortion ..... < 20%
- ETL Listed / UL Standard 496 ..... Yes
- FCC Compliance ..... Part 18, Subp. C
- Warranty ..... 5 Year

## RETROFIT OPTIONS



## REPLACEMENT INFORMATION

Existing Light Source	Existing Wattage	LED Replacement Wattage	Min. Can Size Needed	MODEL NO.
CFL	26	13	8 inch	LED-PL013