



## **CLP-ACRN Series Architectural LED Fixture**



**CLP-ACRN** architectural LED Fixture, suitable for wet locations. Perfect for lighting up residential exteriors, Walkways, Perimeters, School Campuses, Industrial / Commercial Spaces, Parking Lots, Recreational Parks. This fixture has a wide light distribution. Comes with a 10 year warranty.

## FEATURES.

- •Energy Savings: Over 66% compared to HID light sources
- •Improved lumen maintenance
- •High efficient Phillips Lumiled LED's
- •Operating temperatures: -30°C ~ 60°C
- Driver: Constant current, 120-277v, 50/60Hz, 480v (Optional)
- Suitable for wet locations
- Dimming, Occupancy Sensors, Photo Cell and Wireless Controls capable (optional)
- Operating Life: >200,000 hours

## CONSTRUCTION.

- Housing is Heavy-Duty Cast Aluminum Base
- Powder Coat Bronze Finish (Standard). Various colors available (custom).
- Clear Prismatic Acrylic Type 5 (Standard), Clear Prismatic Polycarbonate Lens (optional)
- Silicone Gasket to prevent leakage and provide weather-tight protection.
- Mounting: Comes ready to mount Over 3"O.D Tenon or Pole (Standard), for 4" O.D, Pole Adapter is Required (Optional)

2.3 22 lbs. WEIGHT



CAT#	CAGE	FITTER	HARD TOP	LENS	WATTS	ССТ	VOLTAGE	FINISH	OPTIONS
CAT# CLP-ACORN (CLP-ACRN)	CAGE 1 (CG1)  CAGE 2 (CG2)	FITTER 1 (FT1)  FITTER 2 (FT2)  FITTER 3 (FT3)  FITTER 4 (FT4)  FITTER 5 (FT5)  FITTER 6 (FT6)	TOP 1 (TP1) TOP 2 (TP2) TOP 3 (TP3)	ACTYLIC LENS. LARGE LENS A (LLA)  SMALL LENS A (SLA)  LENS B (LB)  LENS C (LC)  LENS D (LD)  LENS E (LE)  Glass Lens.  LENS GA	WATTS  25W(25CLED)  40W(40CLED)  60W(60CLED)  80W(80CLED)	2700K 27K) 3000K (30K) 3500K (35K) 4000K (40K) 5000K (50K) 5700K (57K) 6500K (65K)	120-277V (MV) 347-480V (48V)	Bronze (BZ) Gray (GRY) Black (BK) White (WH) Custom (CST)	Motion Sensor (OCS) Button Photo Cell (PC) Wireless controls (WC) Type 3 lens (TYP3) Type 5 lens (TYP5) Polycarbonate Lens (PLY)  Decorative Finial Finial 1 (FNL1) Finial 2 (FNL2)

## **CLP-ACRN Series**



CLP-ACRN-FT1-LA

Standard shown



CAGE 1











**DECORATIVE BASE FITTERS** 











SMALL & LARGE LENS A

**GLASS LENS** 

**LENS B** 

**LENS C** 

**LENS E** 





**LENS GA** 







**HARD TOP 1** 

**HARD TOP 2** 

**HARD TOP 3** 

FINIAL 2

**FINIALS** 

Model Number	INPUT POWER	LUMEN OUTPUT	SCOPTIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID Equivalent
CLP-ACRN-20CLED	25W	2,750	4,530	5000K	70+	>200,000	120-277V	50/60HZ	100w MH
CLP-ACRN-40CLED	45W	5,504	8,806	5000K	70+	>200,000	120-277V	50/60HZ	150w HPS
CLP-ACRN-60CLED	65W	8,256	13,622	5000K	70+	>200,000	120-277V	50/60HZ	250w PSMH
CLP-ACRN-75CLED	80W	9,590	15,344	5000K	70+	>200,000	120-277V	50/60HZ	250w HPS

All products are proudly manufactured and/or assembled in the USA