


DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

CLP-MP

Architectural LED Post-op Fixture



The CLP-MP is designed to bring efficiency while transforming the appearance of locations such as, convention centers, shopping centers, museums, entrances, walkways and any other exterior setting that seeks a modern, sophisticated look. This fixture is dark sky compliant and includes a wide light distribution.

FEATURES

- Life Rating: >200,0000 (L70) hours for enhanced safety and mainte-
- 80% compared to HID light sources
- IP55, Suitable For Wet Locations
- Light Output: 5000K
- Voltage: Standard 120-277V
- Applications: Entrances, Walkways, Convention Centers, Shopping Centers, Museums
- 10 Year Warranty
- Philips LED's and driver
- 10 KV Surge Protector
- 3 Mountain Screws for Secure Mounting







CONSTRUCTION

- Clear Tempered Glass
- Heavy Duty Aluminum Body

Model Number	INPUT POWER	LUMEN OUTPUT	SCOPTIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID Equivalent
CLP-MP-5CLED	7W	757	1,249	5000K	70+	>200,000	120-277V	50/60Hz	35w HPS
CLP-MP-10CLED	12W	1,376	2,270	5000K	70+	>200,000	120-277V	50/60Hz	50w HPS
CLP-MP-15CLED	20W	1,918	3,068	5000K	70+	>200,000	120-277V	50/60Hz	70w HPS
CLP-MP-21CLED	25W	3,102	4,963	5000K	70+	>200,000	120-277V	50/60Hz	100w HPS
CLP-MP-30CLED	35W	4,128	6,604	5000K	70+	>200,000	120-277V	50/60Hz	150w HPS

Ordering Guide Example: (CLP-MP-30CLED-50-MV-BZ-WC)

CLP-MP					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
CLP-MP	5W-5CLED	27-2700K	MV=120-277V	BZ-BRONZE	HSS-HOUSE SIDE
	10W-10CLED	30-3000K	480=480V	GRY-GRAY	SHIELD
		35-3500K	480–480 V	GRY-GRAY	EMR-EMR BATTERY
	15W-15CLED	40-4000K		BLK-BLACK	WC-WIRELESS CON-
	21W-21CLED	50-5000K		WH-WHITE	TROL
	30W-30CLED	57-5700K		WII-WIIIIE	PC-PHOTO CELL
		65-6500K		CUS-CUSTOM	