




\*\* AVAILABLE \*\*

0 - 10V

FULL DIMMING



Incredible **100,000 hrs**

## GENERAL DESCRIPTION

Neptun's LED Wall Pack fixtures feature architectural design and durability to fit new construction and retrofit applications. The LED-407 series features high output LED's and custom engineered optics to provide excellent uniformity and efficiency. They can replace existing HID & HPS fixtures up to 250W.

## APPLICATION

- Building Accent Lighting
- Landscape Lighting
- Security Lighting
- Parking Lot Lighting
- Area Lighting
- Storage Area Lighting
- Stairwell Lighting
- Passageway Lighting

## STRUCTURE, MATERIALS, & FEATURES

- Heavy-gauge, die-cast aluminum housing.
- Heat and impact resistant sealed glass lens around optics.
- Corrosion resistant electrocoat dark bronze finish (custom colors available).
- Correlated Color Temperature of (5000°K) for greater visibility and safety.
- High Output COB LED's with borosilicate glass lens optics.
- High power factor, low THD driver with 6kV/3kA surge protection.
- Optional 20kV/10kA surge protector available.
- InstantON flicker-free Cold Start and Hot Re-Start.
- Up to 15 years Maintenance free operation.
- 5 Year Warranty on complete fixture. (LED's, Driver, & Housing)
- **Optional:** 0-10V Dimming, Remote Monitoring and ON/ OFF Control, DC 24V Operation - Solar Compatible

## ORDERING INFORMATION

Sample Number: LED-407100-UNV-0-10VDIM-850-BRZ  
Custom options and accessories available. Please consult factory

| Series              | Wattage                    | Voltage  | Options  | Color Temp   | Accessories                    | Color                                     |
|---------------------|----------------------------|--|--|--|--------------------------------|---|
| LED-407 = Wall Pack | 100 = 100 W<br>120 = 120 W | UNV = 120-277 VAC<br>347V = 347 VAC<br>480V = 480 VAC<br>24VDC = 24VDC | 0-10VDIM = 0-10V Dimming<br>** Contact Factory for dimming options | 835 = 3500°K<br>841 = 4100°K<br>850 = 5000°K *<br>* Standard | SP = 20kV/10kA surge protector | BRZ = Bronze<br>* Custom Colors Available |



## PRODUCT INFORMATION

| Model No.      | Description           | Rated Watts | Input Watts | Delivered Lumens | Universal Line Voltage (VAC) | Max Line Current (Amp) @ 120 - 277 | THD  | Power Factor | Weight |
|----------------|-----------------------|-------------|-------------|------------------|------------------------------|------------------------------------|------|--------------|--------|
| LED-407100-UNV | LED Wall Pack Fixture | 100         | 101         | 12,000           | 120-277                      | 0.87 - 0.37                        | <20% | >0.90        | 30 lbs |
| LED-407120-UNV | LED Wall Pack Fixture | 120         | 121         | 14,400           | 120-277                      | 1.05 - 0.45                        | <20% | >0.90        | 30 lbs |

## SPECIFICATIONS

- Driver ..... Constant Current
- Start Method ..... InstantON
- Hot Re-start ..... InstantON
- Power Supply ..... 350mA
- Driver UL Rating ..... Class 1
- Driver UL Outdoor Rated ..... Wet Location
- Sound Rating ..... Class A
- ANSI Surge Protection ..... IEEE C62.41 C High
- Driver Off-State Draw ..... 0 Watts
- Universal Input Line Voltage ..... 120-277 VAC
- Input Line Frequency ..... 50/60 Hz
- Projected (L70) @ 25°C ..... > 100,000 hrs.
- Color Temperature ..... 5,000°K
- Color Rendering Index (CRI) ..... > 80
- Minimum Starting Temperature ..... -40°C
- Maximum Starting Temperature ..... +50°C
- Lumens per Watt ..... > 100
- Shock / Vibration Resistant ..... Yes
- Power Factor ..... > 0.90
- Total Harmonic Distortion ..... < 20%
- Inrush Current Peak ..... < 10 Amp
- FCC Compliance ..... Part 15, Subp. C
- Driver IP Rating ..... IP67
- Optics IP Rating ..... IP68
- Warranty ..... 5 Year

## MOUNTING OPTIONS

Wall Mount



## PHOTOMETRICS (See Complete IES File)

Type 3 Distribution

