



Description

Our Streetlights are becoming the primary selection for governments around the world looking to brighten their roads. Topped with an unmatched 10-year wrap around warranty and 150 lumens per watt, the exquisite design of the model is only matched by its illuminance on the asphalt.

Applications

Highways
Freeways

Neighborhoods
Streets

Roads

Details

IP Rating
Material
Lens
EP Rating
L70 Life
Warranty
CRI
Certification
Driver Man.
Chip Man.

IP65
Die Cast Aluminum
Tempered Glass
0.32
100,000 Hours
10 Years
80+
UL, FCC, CE, RoHS, UFC
Mean Well
Phillips

Electrical

Power Factor
Frequency
Max THD (%)
Operating Temp.

0.99
50/60 Hz
10
-31° F to 113° F
-35° C to 45° C
Optional

Dimming

	30W & 60W	90W
Length:	20.5 in / 520 mm	28.7 in / 730 mm
Width:	8.6 in / 220 mm	11.6 in / 295 mm
Height:	4.9 in / 125 mm	5.5 in / 140 mm
Weight:	8.6 lb / 3.9 kg	16.9 lb / 7.6 kg



ALTECH MODEL #:	AE-L-SLNG-30	AE-L-SLNG-60	AE-L-SLNG-90
DLC #:	U-SLS-30	U-SLS-60	U-SLS-90
DLC Partner:	Ultron Industries		
Input Wattage:	30W	60W	90W
Equivalent:	175W MH	250W MH	375W MH

Ordering Information

Example: AE-L-SLNG-30-130-50K-1-MS-GR

Wtg	Lumen Pckge	Color Temp.	Input Voltage	Options	Finish
30 60 90	130 L/W*	30K - 3000K 40K - 4000K 50K - 5000K* 57K - 5700K	1 - 120-277V*	MS - Motion Sensor P - Photocell EI - Emergency Inverter	GR - Gray* BZ - Bronze W - White BL - Black SP - Other

*Standard

Standard Color

Gray

Custom Colors

Bronze

White

Silver

Black

Orange

Brown

Blue

Green

Red



Notes:

- Only 5000K in GRAY are in stocked locally, check for ETA's



Lumen Output

System Watts	LPW	Total Lumens
30	130	3,900
60	130	7,800
90	130	11,700



Phenix External Emergency Inverter (18470X-3)

Dimensions

