

DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

OPTIONS

(OCC) motion sensor

(WC) wireless control (PLY) polycarbonate lens

(PC) photocell

LED Post Op



The all-new LED, CLP-SL-M58, has a sophisticated and unique design. It is ideal for illuminating spaces such as: parking areas, entrances, walkways, parks, etc. While suitable for wet locations, this light fixture also offers a wide light distribution. A 10 year warranty is included along with the investment of a CLP-SL-M58.

FEATURES

- Energy Savings: Over 66% compared to HID light sources
- Improved lumen maintenance
- Utilizes high efficient Lumileds Luxeon LED's
- Operating temperatures: $-30^{\circ}\text{C} \sim 60^{\circ}\text{C}$
- Driver: Constant current, 120-277v, 50/60Hz, 480v (Optional)
- Suitable for wet locations
- Dimming, occupancy sensors, photo cell and wireless controls capable (optional)

CONSTRUCTION

- Housing is heavy-duty die-cast aluminum & spun aluminum materials
- Powder coat bronze finish (standard), various colors available (custom w/adder)
- Clear prismatic acrylic Type 5 (standard), polycarbonate lens (optional w/ adder)
- Silicone gasket to prevent leakage and provide weather-tight protec-
- Mounting: Comes ready to mount on top of a 3" round pole (standard)









MODEL#	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID EQUIVALENT
CLP-SL-M58-25LED	30W	3,785	6,245	5000K	70+	>200,000	120~277V	50/60Hz	150w PSMH
CLP-SL-M58-35LED	40W	5,170	8,530	5000K	70+	>200,000	120~277V	50/60Hz	175w HPS
CLP-SL-M58-50LED	55W	6,880	11,352	5000K	70+	>200,000	120~277V	50/60Hz	250w MH
CLP-SL-M58-75LED	80W	9,590	15,823	5000K	70+	>200,000	120~277V	50/60Hz	250w HPS



Ordering Guide Example: CLP-SL-M58-35LED-50-T4-MV-3"-BZ

CLP-SL-M58						
MODEL	WATTS	COLOR TEMP	VOLTAGE	DISTRIBUTION	MOUNTING	FINISH
CLP-SL-M58	25W-25LED	27-2700K	MV=120~277V	STANDARD:	3" ROUND POLE	STANDARD:
	35W-35LED	30-3000K	347=347V	T5-TYPE 5	4" ROUND POLE	BZ-BRONZE
	50W-50LED	35-3500K 40-4000K	480=480V		3" SQUARE POLE	
	75W-75LED	50-5000K		T3-TYPE 3	4" SQUARE POLE	ADD'L COST:
	75 W-75LLD	57-5700K		T4-TYPE 4	5" SQUARE POLE	GRY-GRAY
		65-6500K			6" SQUARE POLE	BLK-BLACK
						WH-WHITE
						CUS-CUSTOM



