



General Description:

The EX-LITE BL series are LED bollards with the latest CCT and wattage selecting technology. It has three different wattages and CCTs all in one bollard.

Construction:

- Corrosion resistant polyester powder coat finish, available in custom colors.
- Cast aluminum structure that resists high shock and vibration.

Electrical:

- Wattage selectable from 12W, 16W & 22W.
- High Power Factor, low THD UL listed driver with 10KV surge protection.
- Universal line voltage input 120-277V, 347/480V optional
- 0-10V dimmable

Optical:

- Ultra wide beam light distribution
- CCT selectable from 30K, 40K & 50K

Warranty:

- 5 years' warranty for complete fixture

Listings:

ETL
FCC
DLC
IP65



Ordering Information:

Shape	Preferred Default Wattage	Preferred Default CCT	Finish Color	Control	Voltage
BLRD (Round)	12W =12W	30K =3000K	(blank)=Bronze, Std	(blank)=none, Std	(blank)=120/277VAC, Std
BLSQ (Square)	16W =16W	40K =4000K	BL =Black	PC =Photocell	HV =347/480VAC
	22W =22W	50K =5000K	WH =White		
			GR =Gray		

PROJECT NAME: _____ CATALOG NUMBER: _____

NOTES: _____ FIXTURE TYPE: _____

Specs:

Shape	Wattage	Lumens	CCT	Height	Width
BLRD (Round)	12W	1440	30K/40K/50K	42"	6.3"
BLSQ (Square)	16W	1920	30K/40K/50K	42"	6.3"
	22W	2640	30K/40K/50K	42"	6.3"

Photometrics:

