LEDSION LED CANOPY LUMINAIRE



Pro-	iect	Inforn	nation
110	Juce	111110111	lucioi

Туре

<u>Name</u>

Voltage

Product Description

LEDSION Canopy Light has a traditional canopy light look design intended for outdoor ceiling mounted applications, combines the brightest 130lm/w above LED technology including IP65 LED driver LED driver and thermal management. high-performance illumination that lasts 50,000HRS, Its ideal for replacing 100-250W metal halide, with typical energy savings of 80%.



Application

General bus station/parking garage.



Electric Characteristic


Specification/Model	LS-NCP55WV2-aaK		
LED Chips	PHILIPS LUXEON 3030 LED		
Input power	55W		
Lumens output	5400-6000LM		
Efficiency	100-115LM/W		
CRI	>75Ra		
Color Temperature	4000K/5000K/5700K		
Input voltage	100-277V 50/60Hz (China Brand Driver)		
Light distribution type	160D		
Working temperature	−20 −+ 45 °C		
Junction temperature	<75℃		
lamps efficiency	≥90%		
Certificates	UL, cUL,DLC		
Equivalent	100-150W MH/HPS		

Ordering Information


Example: LS-NCPXWV2-50K-N-T

Product	Power	Replacement	Color Temperature	Photocell	Furnish
LS-NCP55WV2-aaK	55W	100-150W MH/HPS	40K 4000K		
			50K 5000K	N not photocel	T-White
			57K 5700K		

Packaging



Photometrics




Projected LED Lumen Maintenance

Operating hours	0	25000	50000
Lumen	1	0.91	0.8

Data references the extrapolated performance projections for the Canopy Light platform in a 25°C ambient, based on 10,000 hours of LED testing (tested per IESNA LM - 80-08 and projected per IESNA TM-21-11).

Dimensions: mm



After Sale Service:

The product refers to electrics knowledge. Please don't disassemble it by yourself. If any quality problem happens, please contact the factory for warranty details .

NOTE: Actual performance may differ as a result of end-user environment and application. All values are without notice.