


LFID Toros Linear Fixture

Indoor




Toros Architecture Linear Fixture has a slim and discreet profile, it provides excellent illumination for offices, laboratories, libraries, and commercial spaces. It's available in lengths of 4 ft and 8 ft, and can be joined together in seamless runs of any length.



Luminaire	Toros Architectural Linear Fixture	Type
Project		
Product		
Notes		

- Features**
- Optimal Glare Control, UGR <19
 - Seamless Connection, Tool Free Installation
 - Uniform Illumination, Direct and Indirect Light
 - 6 pieces maximum may be connected at one time



Order Format

Sample: LFID4-33S-3030B8-W

Series	Length	Wattage	Connection Type	CCT Up	CCT Down	Optics	CRI	Finish Color	Options
LFID= Toros	4= 4 ft 8= 8 ft	33=33W 66=66W	S= Continuous Run Starting Fixture M= Continuous Run Middle Fixture E= Continuous Run Ending Fixture C= Stand Alone Fixture	30=3000K 35=3500K 40=4000K	30=3000K 35=3500K 40=4000K	A=80 ° B=120 °	8=80 Ra 9=90 Ra	W=White B=Black S=Silver	S=Sensor E=EM


Application

Available with Cord Pendant, Chain Pendant, Ceiling and T-Profile. Full ability to tandem mount for continuous run application, equipped with male&female quick connect harnesses. 6 pieces maximum may be connected at one time. The cable comes standard 78", but can be custom cut to 24", 48", and 60". For mounting kit, see page 3.

Construction
Die-Formed and Welded Cold Rolled Steel. Painted high reflectance matte white powder coat. Silver oil injection and black powder coat are also provided.

Connectability and Kit

Pg 3



Electrical

The Toros has daylight sensors and EM units as options. All luminaires have been tested by an independent laboratory in accordance with IESNA LM79 and LM80. Product certifications include: ETL, DLC Premium(Pending), CE, and RoHS.

Input Voltage (VAC)	100-277
CRI	80
CCT(K)	3,000, 3,500, 4,000
PF	>.9
THD	<15%
L70 (Hours)	>50,000
Color	White, Black, Silver, Custom
Housing	Cold Rolled Steel
Lens Type	Microprism PPMA 80°, Frosted PPMA 120°
Temperature Range	-20°C to 40°C
Warranty	5 Years

Optics

Highly transmissive PMMA glare control diffuser & frosted cover. Optimal Glare Control, UGR<19

Certifications

- DLC Premium
- ETL
- CE
- RoHS

Lumen Data					
Frosted Acrylic Lens 120°					
Part Number	Wattage (W)	System Wattage	mA, Milliamp	Efficacy (Lm/W)	Lumens (Lm)
				3K	
LFID4-33-X-3030B	33	34.97	750	127	4461
LFID8-66-X-3030B	66	66	1500	127	8421
				35K	
LFID4-33-X-3535B	33	34.97	750	125	4374
LFID8-66-X-3535B	66	66	1500	125	8256
				4K	
LFID4-33-X-4040B	33	34.97	750	122	4288
LFID8-66-X-4040B	66	66	1500	122	8094
Microprismatic 80°					
				3K	
LFID4-33-X-3030A	33	34.97	750	128	4508
LFID8-66-X-3030A	66	66	1500	142	9395
				35K	
LFID4-33-X-3535A	33	34.97	750	126	4420
LFID8-66-X-3535A	66	66	1500	139	9211
				4K	
LFID4-33-X-4040A	33	31.6693	750	136	4333
LFID8-66-X-4040A	66	66	1500	136	9030
Direct Light Only Fixture / Frosted Acrylic Lens 120°					
				3K	
LFDR4-29X-30B8	29	28	650	131	3683
LFDR8-57X-30B8	57	56	1300	131	7366
				3K	
LFDR4-29X-30B8	29	28	650	--	--
LFDR8-57X-30B8	57	56	1300	--	--
				3K	
LFDR4-29X-30B8	29	28	650	--	--
LFDR8-57X-30B8	57	56	1300	--	--


LFID Toros Linear Fixture

Indoor



Dimensions

33W
66W



Part No.	Length (L)	Height(H)	Width (W)
LFID4-33	48	3.4	2.6
LFID8-66	96	3.4	2.6



Recorded in inches

Mounting Options


Connectability

The Toros can be connected by inserting joiner guides and attaching male to female connectors located within fixture sides.


Max Units to Connect: 6 Pieces



Mounting Plates




RC-LFID-02





RC-LFID-01

Mounting Kit


Part Number	Description
RC-LFID-01	Round canopy, $\phi 130 \times 10$ mm, one hole
RC-LFID-02	Round canopy, $\phi 130 \times 10$ mm, two holes (with wire hole)
CK-LFID-24-01	Suspension Cable Kit for Toros Linear Fixture, 24 inch
CK-LFID-48-01	Suspension Cable Kit for Toros Linear Fixture, 48 inch
CK-LFID-60-01	Suspension Cable Kit for Toros Linear Fixture, 60 inch
CK-LFID-78-01	Suspension Cable Kit for Toros Linear Fixture, 78 inch
CK-LFID-120-01	Suspension Cable Kit for Toros Linear Fixture, 120 inch
CK-LFID-150-01	Suspension Cable Kit for Toros Linear Fixture, 150 inch
CK-LFID-180-01	Suspension Cable Kit for Toros Linear Fixture, 180 inch
CK-LFID-240-01	Suspension Cable Kit for Toros Linear Fixture, 240 inch




Mounting Clip




Coverage




**LFID4-33-4K-80°
Prismatic Optic @ 10'**



**LFID4-33-4K-120°
Frosted Acrylic Lens @ 10'**



**LFID8-66-4K-80°
Prismatic Optic @ 10'**



**LFID8-66-4K-120°
Acrylic Lens @ 10'**