

NO.		BL-5050SMD-60P	BL-5050SMD-60P-RGB
	Picture		
1	Input Voltage	100-130V AC	100-130V AC
2	working frequency	50HZ-60HZ	50HZ-60HZ
3	LED Brand	Epistar	Epistar
4	LED Type	5050SMD 3 chips	5050SMD 3 chips
5	LED power	0.2W each	0.2W each
6	Power factory	>0.93	>0.93
7	LED QTY	60pcs LED per meter	60pcs LED per meter
8	LM / LED	20-22LM each LED	20-22LM each LED
9	Power per meter	7-9W Per meter	5-9W Per meter
10	LM/W	60-70LM/W	60-70LM/W
11	Lumen per meter	400-600LM/meter	400-600LM/meter
12	Lifespan	>30,000 hours	>30,000 hours
13	Color Available	Red, yellow, Blue, Green, white, warm white	RGB
14	PCB	White color 8MM PCB	White color 8MM PCB
15	PVC material	Anti-UV PVC 4 to 5 grade	Anti-UV PVC 4 to 5 grade
16		ETL Approval PVC	ETL Approval PVC
17	PVC color	white or clear PVC	white or clear PVC
18	Inside cable	2pcs Pure copper wire 33pcs 0.18 cm ² cable each Total 0.62cm ² each	4pcs Pure copper wire 33pcs 0.18 cm ² cable each Total 0.62cm ² each
20	Size	7*14mm	7*14mm
21	Lens angle	120°	120°
22	Cutting	110V is 0.5 meter per cut	110V is 0.5 meter per cut
23	Maximum Connection Length	110Vcan maximum support 50 meters with one power cord	110Vcan maximum support 50 meters with one power cord
24	Operating temperature	-15°C to +40°C	-15°C to +40°C
25	IP Rate	IP67	IP67
26	Packing	50 meters per roll	50 meters per roll
27	Carton size	50 meters per roll 34*34*15CM Gross weight: 7.5kg per carton	50 meters per roll 34*34*15CM Gross weight: 7.5kg per carton
29	Certificate	CE / RoHs / ETL	CE / RoHs / ETL