

	Item NO.	<b>ILED-BH-O220</b>		Item NO.	<b>ILED-BH-O220-GL</b>
	Input	110-240VAC		Input	110-240VAC
	Watts	7W		Watts	7W
	Size	220*135*65mm		Size	220*135*65mm
	PF	>0.9		PF	>0.9
	Beam Lens	120 Degree		Beam Lens	120 Degree
	Item NO.	<b>ILED-BH-O220-EL</b>		Item NO.	<b>ILED-BH-O280</b>
	Input	110-240VAC		Input	110-240VAC
	Watts	7W		Watts	15W
	Size	220*135*65mm		Size	280*185*100mm
	PF	>0.9		PF	>0.9
	Beam Lens	120 Degree		Beam Lens	120 Degree
	Item NO.	<b>ILED-BH-O280-GL</b>		Item NO.	<b>ILED-BH-O280-EL</b>
	Input	110-240VAC		Input	110-240VAC
	Watts	15W		Watts	15W
	Size	280*185*100mm		Size	280*185*100mm
	PF	>0.9		PF	>0.9
	Beam Lens	120 Degree		Beam Lens	120 Degree
	Item NO.	<b>ILED-BH-S20W/30W</b>		Item NO.	<b>ILED-BH-S20W/30W-TL</b>
	Input	110-240VAC		Input	110-240VAC
	Watts	20W/30W		Watts	20W/30W
	Size	300*300*90mm		Size	300*300*90mm
	PF	>0.9		PF	>0.9
	Beam Lens	120 Degree		Beam Lens	120 Degree