




**\*\* AVAILABLE \*\***

**Bi-Level Dimming**  
100% 50%

**0 - 10V**  
FULL DIMMING



Incredible **100,000 hrs**

## GENERAL DESCRIPTION

Neptun's 15" low-profile round LED canopy fixture features architectural design and durability to be used in new construction or retrofit applications. The LED-LP13 series canopy fixture features excellent optics for increased visibility and security to evenly illuminate parking garages. It can replace existing HID & HPS canopy or parking garage fixtures up to 250 Watts.

## APPLICATION

- Parking Garage Lighting
- Canopy Lighting
- Gas Station Lighting
- Indoor Lighting
- Storage Lighting
- Security Lighting
- Area Lighting

## STRUCTURE, MATERIALS, & FEATURES

- Heavy-gauge, die-cast aluminum housing.
- Corrosion resistant electrocoat dark bronze or white finish.
- Continuous silicone gasket surrounds optics for weather-tight (IP68) seal.
- High Output COB LED's with borosilicate glass lens optics.
- High power factor, low THD driver with 6kV/3kA surge protection.  
Optional 20kV/10kA surge protector available.
- Instant-On flicker-free Cold Start and Hot Re-Start.
- Bright white light (5000°K) for greater visibility and safety.
- LED engine design with Advanced Thermal Management
- Up to 20 year maintenance free operation.
- 10 Year Warranty on complete fixture. (LED's, Driver, & Housing)
- **Optional:** Bi-Level Dimming, 0-10V Dimming, Remote Monitoring and ON/ OFF Control, DC 24V Operation - Solar Compatible

## ORDERING INFORMATION

Sample Number: LED-LP13040-UNV-0-10VDIM-850-ST6-MD-BRZ  
Custom options and accessories available. Please consult factory

Series	Wattage	Voltage	Options	Color Temp	Pendant Length	Accessories	Color
<b>LED-LP13</b> = Low-Profile 15" Round Canopy	<b>040</b> = 40 W <b>060</b> = 60 W <b>080</b> = 80 W	<b>UNV</b> = 120-277 VAC <b>347V</b> = 347 VAC <b>480V</b> = 480 VAC <b>24VDC</b> = 24 VDC	<b>0-10VDIM</b> = 0-10V Dimming <b>BL-DIM</b> = Bi-Level Dimming * * Includes Motion Sensor ** Contact Factory for dimming options	<b>835</b> = 3500°K <b>841</b> = 4100°K <b>850</b> = 5000°K * * Standard	<b>None</b> = Leave Blank <b>ST6</b> = 6" Stem Length <b>ST12</b> = 12" Stem Length <b>ST18</b> = 18" Stem Length <b>ST24</b> = 24" Stem Length	<b>MD</b> = Motion Detector ON/OFF <b>SP</b> = 20kV/10kA surge protector	<b>BRZ</b> = Bronze <b>WHT</b> = White * Custom Colors Available




## PRODUCT INFORMATION

Model No.	Description	Rated Watts	Input Watts	Delivered Lumens	Universal Line Voltage (VAC)	Max Line Current (Amp) @ 120 - 277	THD	Power Factor	Weight
LED-LP13040-UNV	15" Round Canopy	40	42	4,800	120-277	0.34 - 0.15	<20%	>0.90	12 lbs
LED-LP13060-UNV	15" Round Canopy	60	62	7,200	120-277	0.52 - 0.22	<20%	>0.90	12 lbs
LED-LP13080-UNV	15" Round Canopy	80	82	9,600	120-277	0.69 - 0.30	<20%	>0.90	12 lbs


## SPECIFICATIONS

- LED Driver ..... Constant Current
- Power Supply ..... 350mA
- Driver UL Rating ..... Class 1
- Driver UL Outdoor Rated ..... Wet Location
- Start Method ..... InstantON
- Hot Re-start ..... InstantON
- Universal Input Line Voltage ..... 120-277 VAC
- 0-10V Dimming System ..... 100%-0%
- Input Line Frequency ..... 50/60 Hz
- Driver Off-State Draw ..... 0 Watts
- Sound Rating ..... Class A
- ANSI Surge Protection ..... IEEE C62.41 C High
- Projected (L70) @ 25°C ..... > 100,000 hrs.
- Color Temperature ..... 5000°K
- Color Rendering Index (CRI) ..... > 80
- Minimum Starting Temperature ..... -40°C
- Maximum Starting Temperature ..... +50°C
- Lumens per Watt ..... > 100
- Shock / Vibration Resistant ..... Yes
- Power Factor ..... > 0.90
- Total Harmonic Distortion ..... < 20%
- Inrush Current Peak ..... < 10 Amp
- FCC Compliance ..... Part 15, Subp. C
- Housing IP Rating ..... IP65
- Optics IP Rating ..... IP68
- Driver IP Rating ..... IP67
- Warranty ..... 10 Year

## MOUNTING OPTIONS



## PHOTOMETRICS (See Complete IES File)



Horizontal Footcandles  
Scale: 1 Hash = 15 Ft.  
Light Loss Factor = 1.00  
Total Lamp Lumens = 8720.11  
Mounting Height = 15.00 Ft.  
Maximum Calculated Value = 10.81 Fc  
Arrangement: Single

NEPTUN LIGHT, INC.  
LED-LP13080-UNV-850