



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

CLA-3099

Wall-mounted Cylinder



The **CLA-3099** is a wall-mounted cylinder suitable for wet locations. With its up-and-down light features, the **CLA-3099** is perfect for giving extra luminance to any exterior location that wishes to modernize their appearance. This fixture has a wide light distribution and includes a 10 year warranty.

FEATURES

- Energy Savings: Over 66% compared to HID light sources
- Improved lumen maintenance
- Utilizes high efficient Phillips Lumiled LED's
- Operating temperatures: -30°C ~ 60°C
- Driver: Constant current, 120-277v, 50/60Hz, 480v (Optional)
- Suitable for wet locations
- Dimming, occupancy sensors, photo cell and wireless controls capable (optional)
- Optics: 24°, 50°, 78°
- Operating Life: >200,000 hours

CONSTRUCTION

- Housing is heavy-duty aluminum material
- Powder coat bronze finish (standard) various colors available (custom).
- Clear glass lens standard, prismatic glass lens optional
- Silicone gasket to prevent leakage and provide weather-tight protection.
- Mounting: Comes ready to mount on to a standard junction box.

OPTIONS

- (OCC) Motion sensor
- (PC) Button photo cell
- (WC) Wireless controls
- (PG) Prismatic glass



Model Number	INPUT POWER	LUMEN OUTPUT	SCOPTIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID Equivalent
CLA-3099-20CLED	25W	2,752	4,403	5000K	70+	>200,000	120-277V	50/60HZ	150w PSMH
CLA-3099-30CLED	35W	3,836	6,604	5000K	70+	>200,000	120-277V	50/60HZ	175w HPS
CLA-3099-40CLED	45W	5,504	8,806	5000K	70+	>200,000	120-277V	50/60HZ	250w MH
CLA-3099-60CLED	65W	7,672	13,622	5000K	70+	>200,000	120-277V	50/60HZ	250w HPS

Ordering Guide Example: (CLA-3099-30CLED-50-MV-BZ-WC)

CLA-3099					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
CLA-3099	20W-20CLED	27-2700K	MV=120-277V 480-480V	STANDARD FINISH: BZ- BRONZE ADDITIONAL CHARGE: GRY-GRAY BLK-BLACK WH- WHITE CUS-CUSTOM	OCC- MOTION SENSOR PC- BUTTON PHOTO CELL PG- PRISMATIC GLASS WC- WIRELESS CONTROL
	30W-30CLED	30-3000K			
	40W-40CLED	35-3500K			
	60W-60CLED	40-4000K			
		50-5000K			
		57-5700K			
		65-6500K			