



## CVH4AW

4" LED Commercial Frame Housing w/adjustable Wattage and multiple color temperature

### PRODUCT DESCRIPTION

Rouge Lighting Plus **CVH4AW** is a 4" LED Commercial Housing w/adjustable Wattage and multiple color temperature option. Its magnificent interchangeable module and reflector design makes it easy to choose the desired lumen output and color temperature for your projects. Designed for commercial lighting, LED high lumen down light with deep cone reflector. Ideal for new construction applications. LED driver accommodates 120V - 277V inputs with 0-10V dimming standard. CRI ≥80 or ≥90. Long life LED chips guaranteed up to 50,000 hours.



### SPECIFICATIONS/DIMENSIONS

### PRODUCT SPECIFICATIONS

**Commercial Frame** with bar hanger (Included) for tie down to ceiling grids.

**Junction Box** mounted on the frame for easy wire access and driver installation and replacement.

Die-cast aluminum heat-sink dissipates heat from the LED board.

Self-flanged aluminum reflector with a frosted lens to shield direct view from LED, Easy installation with Twist & Lock system and spring clip

3 CCTs / 3 Wattages selectable

0-10V dimming at 120/277V available



cULus Listed

Meets state of California title 24 requirement.

**WARRANTY:** Guaranteed 5 years from the purchase date of the product, against mechanical defects in manufacturing.

### PERFORMANCE DATA

Input Voltage	120V / 277V
Frequency	50 / 60Hz
Operation temp	-30 °C ~40 °C (-22 °F ~104 °F)




## CVH4AW

4" LED Commercial Frame Housing w/adjustable Wattage and multiple color temperature

### Commercial Frame Dimensions

Model NO.	Dimension (L x W x H)	Diameter $\varnothing$
<b>CVH4-AW</b> (4" Plaster Frame)	12-1/8" x 7-5/8" x 3-3/4"	4 3/4"
<b>CVH6-AW</b> (6" Plaster Frame)	12-1/8" x 7-5/8" x 3-3/4"	6 1/4"
<b>CVH8-AW</b> (8" Plaster Frame)	12-1/2" x 9" x 3-3/4"	7 7/8"
<b>CVH10-AW</b> (10" Plaster Frame)	13-5/8" x 13-1/8" x 4"	9 1/8"



### HOUSING ORDERING INFORMATION

SERIES	LUMEN	VOLTAGE	DIMMING	OPTIONS						
CVH4										
CVH4 4" Commercial Frame Housing	<table><tr><td></td><td>16W 1250lm</td></tr><tr><td>AW</td><td>22W 1610lm</td></tr><tr><td></td><td>27W 1950lm</td></tr></table>		16W 1250lm	AW	22W 1610lm		27W 1950lm	blank 120/277V	blank 0-10V dimming	EM Emergency back-up OS Occupancy
	16W 1250lm									
AW	22W 1610lm									
	27W 1950lm									

#### 4 inch

Model No.	Description
CVI4M-83CT	4" LED commercial / Light Module / Heat sink / Twist lock / 16W, 22W, 27W / 3000 / 3500 / 4000K
CVI4S-HZ	4" Reflector / Haze Reflector / White ring / Spring clip / Twist lock
CVI4S-HZHZ	4" Reflector / Haze Reflector / Haze ring / Spring clip / Twist lock
CVI4S-WH	4" Reflector / White Reflector / White ring / Spring clip / Twist lock
CVI4DR-3WT	4" LED Commercial / Driver / Flex. Connector / 120/277V / 0-10V Dimming / 16W, 22W, 27W
CVH4AW	4" LED Commercial / Plaster frame / Need Butterfly clip / Driver with Flex. Conduit connected to J-box directly / 2 power wires / No diecast connector 120/277V / 0-10V Dimming / 16W, 22W, 27W
AVH4AW	4" LED Commercial / Architectural frame / Need Butterfly clip / Driver with Flex. Conduit connected to J-box directly / 2 power wires / No diecast connector 120/277V / 0-10V Dimming / 16W, 22W, 27W

#### 4" Commercial CVI series 80CIR lumen output

4" Reflector + 4" Light Module			
C C T	16 W	22 W	27 W
3000 K	1,190 lm	1,550 lm	1,900 lm
3500 K	1,280 lm	1,680 lm	2,060 lm
4000 K	1,250 lm	1,610 lm	1,950 lm

## REFLECTOR + LIGHT MODULE ORDERING INFORMATION

SERIES	REFLECTOR	MODULE	CCT	FINISH																					
CVI4																									
CVI4 4" commercial Interchangeable trim	S Smooth	<table><tr><td></td><td>16W</td><td>1250lm</td></tr><tr><td>4M</td><td>22W</td><td>1610lm</td></tr><tr><td></td><td>27W</td><td>1950lm</td></tr></table>		16W	1250lm	4M	22W	1610lm		27W	1950lm	<table><tr><td></td><td>3000K 80CRI</td></tr><tr><td>83CT</td><td>3500K 80CRI</td></tr><tr><td></td><td>4000K 80CRI</td></tr><tr><td></td><td>3000K 90CRI</td></tr><tr><td>93CT</td><td>3500K 90CRI</td></tr><tr><td></td><td>4000K 90CRI</td></tr></table>		3000K 80CRI	83CT	3500K 80CRI		4000K 80CRI		3000K 90CRI	93CT	3500K 90CRI		4000K 90CRI	HZ Haze w/White ring HZHZ Haze w/haze ring WH White w/ white ring CW Chrome w/ white ring
	16W	1250lm																							
4M	22W	1610lm																							
	27W	1950lm																							
	3000K 80CRI																								
83CT	3500K 80CRI																								
	4000K 80CRI																								
	3000K 90CRI																								
93CT	3500K 90CRI																								
	4000K 90CRI																								

### LIGHT MODULE (Selectable CCT)




#### Features

- Selectable CCT with built-in switch on the connector
- Effective heat dissipation with aluminum heat sink
- Assemble with Reflector use Twist lock
- Each size of light modules should be used with dedicated driver
- One light module allows for seamless integration of multiple reflector options with easy and tool-free installation.

### Dimensions

CVI4M-83CT (4")



### REFLECTOR




#### Features

- Self-flanged aluminum reflector with spring clip
- Light Module is assembled into the reflector by Twist lock system
- Finish
  - HZ : Haze Reflector / White Ring
  - HZHZ : Haze Reflector / Haze Ring
  - WH : White Reflector / White Ring
  - CWH : Clear Reflector / White Ring

### Dimensions

CVI4S-XX (4")



### POSSIBLE COMBINATION (Housing + Reflector + Light Module)

