



| | |
|-------------|--|
| DATE | |
| PROJECT | |
| TYPE | |
| NOTE | |
| PREPARED BY | |

VL-FB1C3

LED Bullet



The first advantage of the **VL-FB1C3** is that it's a multifunctional installation; it can be mounted with a knuckle mount or a pendant mount. It is ideal for wet outdoor or indoor locations such as: residential, institutional, commercial and multifamily locations. This fixture is energy efficient, durable, and requires low maintenance. The **VL-FB1C3** fixture offers competitive pricing and includes a 3 year warranty.

FEATURES

- Starting Temperature: -30°C ~ 60°C
- Wet location rated
- 4100K
- IP67
- 120~277V
- 80+ CRI
- Operating life: >50,000 hours
- 3 year warranty

CONSTRUCTION

- Tempered clear flat glass lens
- Die-Cast aluminum housing
- Mounting: ½" NPS Knuckle (included), or Pendant Mount with ½" conduit (not included)
- Built-in heat sinks
- Powder coat finish (bronze; standard)
- White reflector

| MODEL # | INPUT POWER | LUMEN OUTPUT | SCOTOPIC | COLOR TEMP (CCT) | CRI | RATED LIFE (L70) | INPUT VOLTAGE | INPUT FREQUENCY |
|----------------|-------------|--------------|----------|------------------|-----|------------------|---------------|-----------------|
| VL-FB1C3-20LED | 20W | 1,800 | 2,970 | 4100K | 80+ | >50,000 | 120~277V | 50/60 Hz |

Ordering Guide

Example: VL-FB1C3-20LED-41-MV-BZ-KN-SF

| VL-FB1C3 | | | | | | |
|----------|-----------|------------|-------------|-----------|--|---|
| MODEL | WATTS | COLOR TEMP | VOLTAGE | FINISH | MOUNTING | OPTIONS |
| VL-FB1C3 | 20W-20LED | 41-4100K | MV-120~277V | BZ-BRONZE | KN-KNUCKLE MOUNT (included) PM-PENDANT MOUNT (not included) | SF-SINGLE FUSE DF-DOUBLE FUSE SP-SURGE PROTECTION |

Dimensions

