

PROJECT	
MODEL #	
TYPE	
DATE	



## LED Hazardous Explosion Proof Fixtures



# ST-HZ-J Family

Class 1 Division 2 hazardous LED lights that can be used in harsh and specialty environments such as gas stations, petroleum and chemical industries, military, airports and marine applications. Designed to withstand the toughest environments while being highly efficient and long lasting.

### FEATURES

- DLC qualified
- IP68 rated
- Color capabilities: 2700K to 6500K
- 5 Year Warranty

### PERFORMANCE RATINGS AND CERTIFICATIONS

UL, CUL, DLC, UL1598A, IP68

### PERFORMANCE SUMMARY

**Lumens:** Up to 23,125  
**Lumens per Watt:** Up to 125  
**CRI-Minimum:** 70  
**CCT:** 2700 - 6500K Available  
**Operating Environment:** -40C to +45C Ambient  
**IP Rating:** IP68  
**Optical Distribution:** 120 degree

### KIT INFORMATION

**Finish:** Aluminum  
**Mounting:** U Bracket  
**Dimensions:** Up to 15.75 " x 15.75 " x 7.29 "

### ELECTRICAL SYSTEM CHARACTERIZATIONS

**Voltage:** 120 - 277VAC  
**Dimming:** No  
**Power Factor:** >0.958  
**Total Harmonic Distortion:** <10%

### WARRANTY

Standard limited 5-year warranty. Optional 10-year warranty available. Contact LLT for more details.

### ST-HZ-J HAZARDOUS FIXTURES PRODUCT FAMILY

Model	Lumens	Watts	Voltage	Dimensions	Color Temp Options
ST-HZ-J-40S	4600	40	MT	7.88" x 7.88" x 10.63"	27=2700K 30=3000K 35=3500K 40=4000K 57=5700K 65=6500K
ST-HZ-J-60	6900	60	MT	11.82" x 11.82" x 6.89"	
ST-HZ-J-80	9200	80	MT	11.82" x 11.82" x 6.89"	
ST-HZ-J-100	11500	100	MT	11.82" x 11.82" x 6.89"	
ST-HZ-J-120	13800	120	MT	15.75" x 15.75" x 7.29"	
ST-HZ-J-150	17250	150	MT	15.75" x 15.75" x 7.29"	
ST-HZ-J-200	23125	185	MT	15.75" x 15.75" x 7.29"	