

DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

## **CLA-MP**











### **Architectural Exterior Wall Fixture**

The **CLA-MP** is designed to bring efficiency while transforming the appearance of locations such as, convention centers, shopping centers, museums, entrances, walkways and any other exterior setting that seeks a modern, sophisticated look. This fixture is dark sky compliant and includes a wide light distribution.

#### **FEATURES**

- Life Rating: >200,0000 (L70) hours for enhanced safety and maintenance
- Energy Savings: 80% compared to HID light sources
- IP55, Suitable For Wet Locations
- Light Output: 5000K
- Voltage: Standard 120-277V
- Applications: Exterior Walls, Entrances, Walkways, Convention Centers, Shopping Centers, Museums
- 10 Year Warranty
- Philips LED's and driver
- 10 KV Surge Protector

### CONSTRUCTION

- Clear Tempered Glass
- Heavy Duty Aluminum Body

Model Number	INPUT POWER	LUMEN OUTPUT	SCOPTIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID Equivalent
CLA-MP-5CLED	7W	757	1,249	5000K	70+	>200,000	120-277V	50/60Hz	35w HPS
CLA-MP-10CLED	12W	1,376	2,270	5000K	70+	>200,000	120-277V	50/60Hz	50w HPS
CLA-MP-15CLED	20W	1,918	3,068	5000K	70+	>200,000	120-277V	50/60Hz	70w HPS
CLA-MP-21CLED	25W	3,102	4,963	5000K	70+	>200,000	120-277V	50/60Hz	100w HPS
CLA-MP-30CLED	35W	4,128	6,604	5000K	70+	>200,000	120-277V	50/60Hz	150w HPS

Ordering Guide Example: (CLA-MP-30CLED-50-MV-CUS-WC)

CLA-MP					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
CLA-MP	5W-5CLED	27-2700K	MV=120-277V	<u>STANDARD</u> :	HSS-HOUSE SIDE SHIELD
	10W-10CLED	30-3000K	480=480V	BZ-BRONZE	EMR-EMR BATTERY
	15W-15CLED	35-3500K			WC-WIRELESS CONTROL
	21W-21CLED	40-4000K		ADDITIONAL CHARGE:	PC-PHOTO CELL
	30W-30CLED	50-5000K		GRY-GRAY	TC-THOTO CLLE
		57-5700K		BLK-BLACK	
		65-6500K		WH-WHITE	
				CUS-CUSTOM	



	DATE	
]	PROJECT	
	TYPE	
	NOTE	
PRI	EPARED BY	

## **CLA-MP**

# **Architectural Exterior Wall Fixture**





