

DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

## **CLAD3-23**





The **CLAD3-23** is suitable for wet locations and is perfect for residential exteriors, walkways, perimeters, recreational parks, and any other location that is looking to refurbish their appearance. The **CLAD3-23** has a wide light distribution. In addition, this fixture is dark sky compliant. Along with your investment, the **CLA3-23** comes with a 10 year/100,000 hour limited warranty.

## **FEATURES**

- Energy Savings: Over 66% compared to HID light sources
- Improved lumen maintenance
- Utilizes high efficient Phillips Lumiled LED's
- Operating temperatures: -30°C ~ 60°C
- Driver: Constant current, 120-277v, 50/60Hz, 480v (optional)
- Suitable for wet locations
- Dimming, occupancy sensors, photo cell and wireless controls capable (optional)



## **CONSTRUCTION**

- Housing is heavy-duty die-cast aluminum
- Powder coat bronze finish (standard) various colors available (custom).
- Opal acrylic lens standard, and other lens options available
- Silicone gasket to prevent leakage and provide weather-tight protection.
- Mounts to a standard wall mount 4-inch junction box

## **OPTIONS**

- (OCC) Motion sensor
- (PC) Button photo cell
- (WC) Wireless controls
- (PG) Prismatic glass





PHILIPS LUMILEDS



Model Number	INPUT POWER	LUMEN OUTPUT	SCOP- TIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID Equivalent
CLAD3-23-5CLED	5W	757	1,211	5000K	70+	>200,000	120-277V	50/60HZ	35w HPS
CLAD3-23-10CLED	10W	1,376	2,201	5000K	70+	>200,000	120-277V	50/60HZ	50w HPS
CLAD3-23-15CLED	15W	1,918	3,068	5000K	70+	>200,000	120-277V	50/60HZ	75w MH
CLAD3-23-21CLED	21W	3,102	4,963	5000K	70+	>200,000	120-277V	50/60HZ	100w HPS
CLAD3-23-40CLED	40W	5,504	8,806	5000K	70+	>200,000	120-277V	50/60HZ	150w HPS

Ordering Guide Example: (CLAD3-23-40CLED-50-MV-BZ-WC)

	Example: (elitibs 25 toella to 11 t B2 tre)							
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS			
CLAD3-23	5W-5CLED 10W-10CLED 15W-15CLED 21W-21CLED 40W-40CLED	27-2700K 30-3000K 35-3500K 40-4000K <b>50-5000K</b> 57-5700K	MV=120-277V 480-480V	STANDARD BZ-BRONZE  CUSTOM (ADD'L CHARGE) GRY-GRAY BLK-BLACK WH- WHITE	PC- BUTTON PHOTOCELL WC- WIRELESS CONTROL			
		65-6500K		CUS-CUSTOM				