Galveston



Architectural LED Luminaire

Galveston Architectural LED Luminaire, suitable for wet locations. Perfect for lighting up Historical Buildings, Parks or Streets, Perimeters, Residential Exteriors, Walkways, or Perimeters, School Campuses, Industrial or Commercial Spaces, Parking Lots, Recreational Parks. This fixture has a wide light distribution.

- 10 year/100,000 hour limited warranty.

Construction.

-Housing is Heavy-Duty Cast Aluminum Base.

-Powder Coat Bronze Finish (Standard). Various colors available (custom).

-Clear Acrylic Lens (Standard), Clear Polycarbonate Lens (optional).

-Silicone Gasket to prevent leakage and provide weather-tight protection.

<u>Mounting:</u> 3.5"O.D Tenon or Pole (Standard), Adapter is Required for other mountings. <u>Light Distribution</u>. Type 5 od Type 3 (Per Order)











<u>LA-HT1</u>

Cat #	Input Power	Lumen Output	LPW	Color Temp. (CCT)	CRI	Rated Life (L70)	Imput Voltage	HID Equivalent
CLP-ACRN-20CLED	25W	3,680	184	5000K	70+	>200,000	120-277V	50W MH
CLP-ACRN-40CLED	45W	6,492	162	5000K	70+	>200,000	120-277V	150W MH
CLP-ACRN-50CLED	55W	7,780	155	5000K	70+	>200,000	120-277V	250W MH
CLP-ACRN-60CLED	65W	8,539	142	5000K	70+	>200,000	120-277V	175W PSMH
CLP-ACRN-80CLED	85W	9,590	119	5000K	70+	>200,000	120-277V	250W PSMH


Average Height and Diameter



Example: GLVTN-TP1-LLA-FNL2-40CLED-T3-30K-MV-BLK-PC









Cat #	Hard Top	Lens/ Finial	Wattage	Light Dist.	Color Temp.	Voltage	Finish	Options
GLVTN								
Galveston (GLVTN)	No HT (NHT) Top 1 (TP1) Top 2 (TP2) Top 3 (TP3) *Lens A-L only	Large Lens A (LLA) Finial 2 (FNL2) No Finial (NFNL)	20W (20CLED) 40W (40CLED) 50W (50CLED) 60W (60CLED) 80W (80CLED)	Type 3 (T3) Type 5 (T5)	3000K (30K) 4000K (40K) 5000K (50K)	120-277∨ (MV) 480∨ (HV)	Black (BLK) White (WHT) Silver (SLR) Bronze (BRZ) Graphite (GPH) Custom (CST)	Occupancy Sensor (OCC) Buttom Photo Cell (PC) 7Pin Photocell Recep- tacle & Shoring Cap (7PCR) (Hard Top Only) Wireless Control

(WC)