

5001

LED Ceiling / Pendant Mount

DESIGN - QUALITY



Crystal 
Lighting

5001

Ceiling/Pendant Mount



5001 is perfect for illuminating interior locations such as: parking garages, canopies, and industrial/commercial spaces. This garage light fixture is designed for wet locations and includes a wide light distribution.

-10 year / 100,000hrs Limited Warranty.


FEATURES.

- Optical System designed for Parking Garages
- Energy Savings: Over 60% compared to HID light sources
- Improved lumen maintenance
- Utilizes high efficient Lumiled LED's
- Operating temperatures: -30°C ~ 60°C
- Driver: 0-10v dimmable programmable Phillips driver, 120-277v, 50/60Hz,
- Suitable for wet locations
- occupancy sensors, photo cell (optional)
- Operating Life: 200,000 hours (L70)


CONSTRUCTION.

- Housing is Aluminum Spun.
- Silicone Gasket to provide IP65 Protection
- 3mils Powder Coat (various colors available.)
- Clear Optic System
- Mounting: Mounting Directly Over a 4" "J" Box on Ceiling or Pendant Mount 12", 24" and 36" Long Stem.


OPTIC DISTRIBUTION




TYPE 2 (T2)



TYPE 3 (T3)



TYPE 4 (T4)



TYPE 5 (T5)






Example: (5001-40CLED-5K-MV-WH-PM15-PC)



CAT #	WATTS	KELVIN	VOLTAGE	FINISH	MOUNTING	OPTIONS
5001 (5001)	20W (20CLED) 30W (30CLED) 40W (40CLED) 60W (60CLED) 70W (70CLED)	3000K (3K) 4000K (4K) 5000K (5K)	MULTI-VOLT (mv)	BRONZE (BRZ) GRAPHITE (GPH) BLACK (BLK) WHITE (WH) CUSTOM (CST)	Ceiling Mount (CM) Pendant Mount 12" (PM12) 24" (PM24) 36" (PM36)	MOTION SENSOR (OCC) BUTTON PHOTO CELL (PC) EMR. BATTERY (EMR) WIRELESS CONTROL(WC)

All products are proudly manufactured and/or assembled in the USA

5001-CM



5001-PM



Dimensions				
CAT#	A	B	C	EPA
5001-CM	16" 1/8	5" 1/4		.53
5001-PM12	16" 1/8	5" 1/4	12	.60
5001-PM24	16" 1/8	5" 1/4	24	.67
5001-PM36	16" 1/8	5" 1/4	36	.74

Cat #	Input Power	Lumen Output	LPW	Color Temp (CCT)	CRI	Input Voltage	Input	Frequency
5001-CM-30CLED	35W	5,222	174	5000K	70+	120-277V		50/60HZ
5001-CM-40CLED	45W	6,496	162	5000K	70+	120-277V		50/60HZ
5001-CM-50CLED	55W	7,320	146	5000K	70+	120-277V		50/60HZ
5001-CM-60CLED	65W	9340	155	5000K	70+	120-277V		50/60HZ
5001-CM-70CLED	75W	9,986	142	5000K	70+	120-277V		50/60HZ