



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-PF81

Enclosed Rounded Large LED Area Light



The **VL-PF81** ensures powerful luminosity and provides security for any given location. It is constructed with robust die cast aluminum and given a clear prismatic lens to seal the LED array. In addition, The **VL-PF81** is designed to fit in various locations such as: residential areas, walkways, driveways and community parks. The **VL-PF81** offers competitive pricing and includes a 5 year warranty.

FEATURES

- Starting Temperature: -40°C ~ 50°C
- CRI: 80+
- Color temp: 5000K
- Driver: Constant current, 120~277V
- Operating life: >50,000 hours
- 5 year warranty



OPTIONS

- SF- Single Fuse
- DF- Double Fuse
- SP- Surge Protection

CONSTRUCTION

- Die-cast aluminum body
- Black finish (standard)
- Clear prismatic array lens to seal LED array

Model Number	Input Power	Lumen Output	Scoptic	Color Temp (CCT)	CRI	Rated Life HRS (L70)	Input Voltage	Input Frequency
VL-PF81-176LED	186W	13,069	21,563	3000K	80+	>50,000	120~277V	50/60Hz
VL-PF81-176LED		13,287	21,924	4000K				
VL-PF81-176LED		14,521	23,960	5000K				

Ordering Guide

Example: VL-PF81-176LED-50-MV-BLK-SF

VL-PF81

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-PF81	176W-176LED	50-5000K	MV—120~277V	BLK—BLACK	SF— SINGLE FUSE DF— DOUBLE FUSE SP— SURGE PROTECTION

Dimensions

