



PRODUCT – IR2 SERIES

Available in 265mA, 430mA, 460mA, LED and universal voltages

UL 844-Class 1 Div 2 Groups A, B, C, D

APPLICATIONS

Petrochemical Facilities
Lubrication Pits
Oil Drilling Rigs
Crew Quarters

Solvent/Cleaning Areas
Processing Plants
Water Treatment Areas
Marine Loading Docks

SPECIFICATIONS

UL LISTING:

CLASS 1, DIVISION 2, GROUPS A, B, C & D
UL 844 Hazardous Locations

NOMENCLATURE

IR2	-	4	-	2	-	80	-
(1)		(2)		(3)		(4)	

(1) Series

IR2

(2) Length

2 – 2 ft Nominal Length

4 – 4 ft Nominal Length

(3) Number of Lamps

2 – two lamps

(4) Ballast Type

26 – 265mA T8

43 – 430mA T12 RS

46 – 460mA T5HO

LED – 4400 Lumens Per 4ft Strip, 2200 Lumens per 2ft Strip

(5) Voltage

12 – 120v 60MHz

22 – 220v 50MHz

24 – 240v 60MHz

27 – 277v 60MHz

UNV – 120/277v 50/60MHz

(6) Mounting Style

O – Standard (End Mounting)

(7) Options

IR2-MKT – Beam Clamps, Safety Cable

EM – Emergency Ballast

LAMPS INCLUDED IN ALL FIXTURES