

Heliport Beacon

AH-HP-B

A heliport beacon should be provided at a heliport where long-range visual guidance is considered necessary and is not provided by other visual means; or identification of the heliport is difficult due to surrounding lights.

The heliport beacon shall be located on or adjacent to the heliport preferably at an elevated position and so that it does not dazzle a pilot at short range.

AH-HP-B flashes white color 4 times/0.8second and stop for 1.2s, then start new circle for 2seconds(0.8s+1.2s).




APPLICATION











Compliance

- ICAO Annex 14 Volume II Heliports 5.3.2
- FAA AC 150/5390-2B Heliport Design Guide
- CAP 437

Features

Electrical

• Xenon as light source, service life more than 10⁸ times

Physical

- Clear polycarbonate lens for converging light and also provides corrosion resistance and UV protection.
- UV protection Powder coated bright yellow color base make better visibility
- Base material is stainless steel 304 which has strong corrosion resistance, Shock and Vibrations protection

Optional

- Controller for power supplying and turn ON/OFF light
- VHF pilot to ground remote control

Application


Helipad/Heliport/Helideck




Heliport Beacon

AH-HP-B

Dimension(mm)





SPECIFICATIONS	AH-HP-B Heliport Beacon
Light Characteristics	
Light Source	Xenon
Available Colors	White
Intensity(cd)	≥2500cd
Horizontal Output(degrees)	360
Vertical Divergence(degrees)	≥10
Flash Characteristics	4 quick flashes in 0.8s, off 1.2s(Morse code "H")
Operation Mode	24hours operation
LED Life Experience(hours)	>100,000
Electrical Characteristics	
Operating Voltage	220-240VAC
Power(W)	15
Circuit Protection	Integrated
Physical Characteristics	
Body Material	UV protected Polycarbonate
Base Material	Powder-coated stainless steel 304
Mounting	100×100×012
Dimension(mm)	158×158×410
Weight(kg)	3.2
Product Life Expectancy	Average 5 years
Environmental Factors	
Ambient Temperature(℃)	-45~80
Humidity	10~90%
Wind Speed	80m/s
Waterproof	IP65
Compliance	
ICAO	ICAO Annex 14 Volume II Heliports 5.3.2
FAA	FAA AC 150/5390-2B Heliport Design Guide
Options Available	
	Power coated color
	VHF Pilot to Ground Remote Control